

PROCEED[®] Smooth Absorbent Texture creates the look of European plaster and can convey rustic and refined, old world and contemporary looks rich in texture. It is an opaque acrylic mastic texture coating formulated with fine absorbent aggregates of uniform size, and requires minimal preparation to correct minor surface blemishes and drywall seams. This product is one of a family of compatible textures that can be used alone or blended with others to achieve a wide range of surface appearance.

PROCEED[®] Textures are formulated with 100% acrylic polymers and are compatible with most waterborne products. However, test mixes and sample boards should always be employed to ensure compatibility and performance.

DO NOT USE with solvent-based materials.

PROCEED[®] Smooth Absorbent Texture

PRODUCT APPLICATION

PROCEED[®] Smooth Absorbent Texture is a versatile finishing plaster that can create a wide range of textural effects. It produces a smooth, absorbent surface, with a fine, uniform relief that readily accepts paints and glazes, while retaining a “dry” matte finish.

Apply to a clean and dry substrate using a roller designed for thick materials or with a trowel. PROCEED[®] Textures do not require the application of a scratch coat for adhesion. Apply at rate of 70 - 80 sq ft / gallon to conceal surface irregularities of the substrate or to cover holes and minor cracks. Subsequent coats may be applied if desired. PROCEED[™] Textures may be thinned with water to adjust the application consistency.

Trowel or tool the texture to the desired appearance. This material contains no crushable aggregates and will not change texture as it is worked. It may be troweled to a low-profile surface or stippled for maximum coarseness.

Let dry 12 - 24 hours before over coating with other PROCEED[™] products. Full hardness is developed in 2 - 4 weeks.

TINTING:

Tint with **PROCEED[®] Pigment Dispersions**, or **PROCEED[®] Slow-Drying Fluids** if a weaker tint is desired, mixing thoroughly before use. Do not add more than 10% dispersion or Slow-Drying Fluid in combination by volume. Use of more than recommended percentage could cause a change in application characteristics or (in the case of dispersions) water sensitivity in the dried finish. Always test tint ratio for desired color before use.

ADDITIONAL INFORMATION:

Always use safe work practices. Avoid ingestion, excessive skin contact and inhalation of concentrated vapors.

Store between 50 and 80 degrees Fahrenheit. DO NOT FREEZE. If frozen repeatedly, the product may become unusable.

MANUFACTURED BY

GOLDEN
ARTIST COLORS[®]

Golden Artist Colors, Inc.
188 Bell Road
New Berlin, NY 13411 USA
607-847-6154
www.goldenpaints.com

The above information is based on research and testing done by Golden Artist Colors, Inc., and is provided as a basis for understanding the potential uses of the products mentioned. Due to the numerous variables in methods, materials and conditions of producing art, Golden Artist Colors, Inc. cannot be sure the product will be right for you. Therefore, we urge product users to test each application to ensure all individual project requirements are met. While we believe the above information is accurate, WE MAKE NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, and we shall in no event be liable for any damages (indirect, consequential, or otherwise) that may occur as a result of a product application.