

**PROCEED® Smooth Light-Bodied Texture** is a medium for all techniques used to create a highly absorbent, high relief surface, as well as soft textures such as faux leather.

PROCEED® Textures are formulated with 100% acrylic polymers and are compatible with most waterborne products. However, test mixes and sample boards should always be employed to ensure compatibility and performance.

**DO NOT USE with solvent-based materials.**

## PROCEED® Smooth Light-Bodied Texture

### PRODUCT APPLICATION

**PROCEED® Smooth Light-Bodied Texture** is an opaque acrylic texture that incorporates low-density aggregates. Unlike other textures, this medium dries to a softer, more resilient finish that yields to pressure. This film characteristic allows the creation of faux leather and other finishes that rely on tactile sensations to create a more complete illusion. The resiliency of the material enhances sound absorption, making it an ideal texture to use in situations such as home theater installations where materials and room furnishings are selected to control reflected sound.

Apply to a clean and dry substrate using a roller designed for thick materials or with a trowel. Tool the texture to the desired appearance. PROCEED® Textures do not require the application of a scratch coat for adhesion. Subsequent coats may be applied if desired. PROCEED® Textures may be thinned with water to adjust the application consistency.

Let dry 12 - 24 hours before over coating with other PROCEED® products. Full hardness is developed in 2 - 4 weeks.

### TINTING:

Tint with **PROCEED® Pigment Dispersions** or **PROCEED® Slow-Drying Fluids** if a weaker tint is desired, mixing thoroughly before use. Always test tint ratio for desired color before use. Do not add more than 10% dispersion or Slow-Drying Fluid in combination by volume. Use of more than the recommended percentage could cause changes in application characteristics and (in the case of dispersions) water sensitivity in the dried finish.

### ADDITIONAL INFORMATION:

Always use safe work practices. Avoid ingestion, excessive skin contact, and inhalation of concentrated vapors and sanding dusts. Clean tools with soap and water.

**Store between 50 and 80 degrees Fahrenheit. DO NOT FREEZE. If frozen repeatedly, the product may become unusable.**

MANUFACTURED BY

**GOLDEN**  
ARTIST COLORS®

Golden Artist Colors, Inc.  
188 Bell Road  
New Berlin, NY 13411 USA  
607-847-6154  
[www.goldenpaints.com](http://www.goldenpaints.com)

The above information is based on research and testing done by Golden Artist Colors, Inc., and is provided as a basis for understanding the potential uses of the products mentioned. Due to the numerous variables in methods, materials and conditions of producing art, Golden Artist Colors, Inc. cannot be sure the product will be right for you. Therefore, we urge product users to test each application to ensure all individual project requirements are met. While we believe the above information is accurate, WE MAKE NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, and we shall in no event be liable for any damages (indirect, consequential, or otherwise) that may occur as a result of a product application.